



Novel Tech Enviro Limited
新環科有限公司

工商業用抽濕機 Industrial/Commercial Dehumidifier

GERMAN  ELECTRIC



座地式 Stand Type

- 抽濕機型號 Model : **GE360-CB3**
- 除濕量 Dehumidifying Capacity 30C/80%RH : **360 升/日 L/D**
- 額定輸入功率 Rate Power : **5000 W**
- 最大功率 Max Power : **6500 W**
- 額定電源 Power Supply : **3~/380V/50Hz**
- 額定電流 Rate Current : **9.5 A**
- 循環風量 Circulating Air : **3800m³/h**
- 外型尺寸 Dimension : **980mm (W) x 472 mm (D) x 1720mm (H)**
- 制冷劑 Refrigerant : **R-417a/3350g (環保雪種)**
- 濕度控制器 Humidity Control : **設定範圍 Humidity setting range 10%RH - 90%RH**
- 抗菌濾網 : **於濾網、冷凝器片、風輪扇葉加噴 (日本制做) 水觸媒 (專、抗菌防黴塗膜，有效抗菌防黴)**
- Anti-Bacteria Filter : **Antimould, antibacterial, keep environment clean (Made in Japan)**
- BN6 散熱塗層 : **於壓縮機加上 BN6 散熱塗層：加強散熱效能，使壓縮機更持久耐用**
- BN6 Thermal Conductive Coating : **BN6 Thermal Conductive Coating significantly improve conductivity of heat transfer material. By allowing better heat transfer, it'd help increase hardware performance on efficiency, reduce potential repair and increase life span on components such as compressor.**
- 排水口直徑 Drainage Diameter : **3/4 吋 Inches**
- 適用面積 : **4000-5500 平方呎 (以 8 呎至 10 呎樓底高度計算)**
- Applying Area : **4000-5500 sq. ft. (Based on 8 ft. - 10 ft. height from Floor to Ceiling)**
- 重量 Weight : **158 Kg**
- 功能特點 : **微電腦全自動濕度控制功能、當前環境濕度 LCD 液晶顯示、高效自動化霜系統 (低溫適用)、1-24 小時關機功能，連續排水 (需要安裝去水喉管)。**
- Functions : **Microcomputer control, humidity LED digital dynamic display. Low temperature applicable, efficient automatic defrosting system. 1-24h timer function. Need to be fitted water pipes.**
- 保養 : **一年保養、三年壓縮機、第一年提供一次免費上門檢查**
- Warranty : **1 year warranty, 3 year compressor warranty, provide one time free inspection for 1st year**



Unit A, 3/F, Tai Chiap Factory Building, 17 Yuk Yat Street, To Kwa Wan, Kowloon, Hong Kong.
香港九龍土瓜灣旭日街 17 號泰捷工廠大廈 3 樓 A 室

Tel: (852) 2729 9111 Fax: (852) 3005 4951 E-mail: nte1010@yahoo.com.hk