



工商業用抽濕機 Industrial/Commercial Dehumidifier

GERMAN  ELECTRIC



座地式 Stand Type

抽濕機型號 Model :

GE60-COM

除濕量 Dehumidifying Capacity 30C/80%RH :

60 升/日 L/D

額定輸入功率 Rate Power :

730 W

最大功率 Max Power :

900 W

額定電源 Power Supply :

1~220V/50Hz

額定電流 Rate Current :

3.3 A

循環風量 Circulating Air :

300 m³/h

外型尺寸 Dimension :

350mm (W) x 380mm (D) x 660mm (H)

制冷劑 Refrigerant :

R-417a/380g (環保雪種)

濕度控制器 Humidity Control :

設定範圍 Humidity setting range 10%RH - 90%RH

抗菌濾網 :

於濾網、冷凝器片、風輪扇葉加噴(日本制做)無機金屬觸媒(專、抗菌防黴塗膜,有效抗菌防黴

Anti-Bacteria Filter :

Antimould, antibacteria, keep environment clean (Made in Japan)

BNG 散熱塗層 :

於壓縮機加上 BN6 散熱塗層:加強散熱效能,使壓縮機更持久耐用 **BNG Thermal Conductive Coating significantly improve conductivity of heat transfer material. By allowing better heat transfer, it'd help increase hardware performance on efficiency, reduce potential repair and increase life span on components such as compressor**

BNG Thermal Conductive Coating :



排水口直徑 Drainage Diameter :

1/2 吋 Inches

適用面積 :

600-1000 平方呎 (以 8 呎至 10 呎樓底高度計算)

Applying Area :

600-1000 sq. ft. (According to 8 ft. - 10 ft. height from Floor to Ceiling)

重量 Weight :

28 Kg

儲水箱 :

7 升 (可安裝去水喉管,無需滿水時浪費人手傾倒水桶)

Water Tank Capacity :

7 L (Continuous drains continuous drainage)

功能特點 :

全自動濕度控制功能、當前環境濕度 LCD 液晶顯示、高效自動化霜系統(低溫適用)、1-24 小時關機功能、高低兩段風速選擇,底部裝有方向輪,可自由移動。

Functions :

Humidity automatic control, humidity LED digital dynamic display. Low temperature applicable, efficient automatic defrosting system. 1-24h timer function. High and low 2 speed adjustable. At the bottom equipped with caster, move freely

保養 :

一年保養、三年壓縮機、第一年提供一次免費上門檢查(適合工商業客戶)

Warranty :

1 year warranty, 3 year compressor warranty, provide one time free inspection for 1st year (for commercial/industrial client)

Unit A, 3/F, Tai Chiap Factory Building, 17 Yuk Yat Street, To Kwa Wan, Kowloon, Hong Kong.

香港九龍土瓜灣旭日街 17 號泰捷工廠大廈 3 樓 A 室

Tel: (852) 2729 9111

Fax: (852) 3005 4951

E-mail: nte1010@yahoo.com.hk

www.nte.com.hk